


## **Product Data Sheet** GW44206





Range 44 CE - Surface-mounting waterthight junction boxes in compilance with EN 60670-1 (CEI 23-48) and IEC 60670-22 (CEI 23-94) and made in high-performance technopolymers. The range includes versions with protection degree IP44, IP55, IP56 with smooth walls or with quick entry cable glands and different type of covers: blind / transparent, deep/plain, press-on/screw (in plastic, also 1/4 turn, or in metal). Available in different self-extinguishing materials (up to GWT 960 °C). Suitable for ordinary junctions, for special uses, and for industrial uses.

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS										
Saline solution	Acids		Bases		Solvents				Mineral	UV
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol	oil	rays
R <mark>esista</mark> nt	L <mark>imite</mark> d resistance	Resistant	Resistant	Resistant	L <mark>imite</mark> d resistance	Not resistant	Not resistant	L <mark>imite</mark> d resistance	L <mark>imite</mark> d resistance	L <mark>imite</mark> d resistance

## **DIMENSIONAL**







**TECHNICAL SYMBOLOGY** STANDARDS/APPROVALS





